


## Data sheet: Wilo-Multivert MVI 118 (3~400 V, EPDM, PN 25)



### Pump curves



Pump curves in accordance with ISO 9906, class 2

### Terminal diagram

#### Three-phase current ≤ 4 kW



### Power

Fluid temperature	$T$	-15...+120 °C
Max. ambient temperature	$T$	40 °C
Maximum operating pressure	$p_{max}$	25 bar

### Minimum Efficiency Index (MEI)

Minimum Efficiency Index (MEI)	≥ 0.40
--------------------------------	--------

### Motor

Insulation class	F	
Protection class	IP 55	
Mains connection	3~400 V, 50 Hz	
Nominal motor power	$P_2$	2.2 kW
Power consumption	$P_1$	2.64 kW
Nominal current 3~230 V, 50 Hz	$I_N$	8.0 A
Nominal current 3~400 V, 50 Hz	$I_N$	4.6 A
Motor efficiency	$\eta_m$ 50%	82.0 %
Motor efficiency	$\eta_m$ 75%	83.2 %
Motor efficiency	$\eta_m$ 100%	83.2 %

### Connections

Flange nominal diameter (on the pressure side)	DN 25	
Flange nominal diameter (on the suction side)	DN 25	
Rated pressure level (on the pressure side)	$PN$	PN 25
Rated pressure level (on the suction side)	$PN$	PN 25

### Materials

Impeller	1.4301 [AISI304]
Pump housing	1.4301 [AISI304]
Pump shaft	1.4301 [AISI304]
Static seal	EPDM
Mechanical seal	U3BE3GG

### Information for order placements

Make	Wilo
Type	MVI 118
Art no.	4070491