



MH9

Technical data 50Hz

Pump model		NUMBER OF STAGES	MOTOR POWER		INPUT POWER	INTERNAL CAPACITOR		RATED CURRENT			
Single-phase 220-240V 50Hz	Three-phase 380-415V 50Hz		kW	HP	kW	µF	V	Single-phase 220-240V 50Hz		Three-phase	
								220-240V 50Hz	380-415V 50Hz	220-240V 50Hz	380-415V 50Hz
MH 9/2	MH 9/2T	2	0,75	1	0,90	16	450	4,3	3,1	1,8	
MH 9/3	MH 9/3T	3	1,1	1,5	1,37	30	450	6,4	4,7	2,7	
MH 9/4	MH 9/4T	4	1,5	2	1,77	30	450	8,2	6,1	3,5	
-	MH 9/5T	5	1,85	2,5	2,21	-	-	-	6,9	4,0	
-	MH 9/6T	6	2,2	3	2,61	-	-	-	7,8	4,5	

- Single-phase motors: 220-240 V ± 5 % / 50 Hz. Thermal protection built into the motor.
- Three-phase motors: 380-415 V ± 5 % / 50 Hz. Thermal protection to be provided into the starter panel by the installer.

Dimensions and weights

Pump model		Dimensions							PACKAGING					
Single-phase 220-240V 50Hz	Three-phase 380-415V 50Hz	A mm	E mm	C mm	D mm	F mm	G		DN1	DN2	L mm	B mm	H mm	Weight kg
							1-phase	3-phase						
MH 9/2	MH 9/2T	118	260	158.6	192	378	134	118	1 1/2	1 1/4	500	200	260	10,8
MH 9/3	MH 9/3T	118	260	158.6	192	378	134	118			500	200	260	12,8
MH 9/4	MH 9/4T	148	304	188.6	222	452	125	125	1 1/2	1 1/4	610	220	260	16,5
-	MH 9/5T	178	304	218.6	252	482	125	125			610	220	260	17,2
-	MH 9/6T	208	304	248.6	282	512	125	125			610	220	260	17,8

- All connections threaded BSPP.

