SW(PRO)- RANGE

SEWAGE SUBMERSIBLE PUMP



SW (PRO) - Range

Main Application: Discarge Waste Water, Rainwater and Sewage Water

Motor: 30% DownIPX8 Protection Level and F-Level Insulation

Shaft Seal: Oil Filled

Cable: Sewage-Resistant Flexible Cable with Rubber Sheath



5.5 15 65 PRO S SW 80

- Power (kW)
- Rated Head (m)
- Rated Flow (m^3/h)
- No Blockage Cutting Type
- Stainless Steel Corrosion Resistant Type
- Sewage Submersible Pump
- Discharge Diameter (mm)

SW-PRO (WQW) Cast Iron Automatic Coupling Mounting Dimension

Pump Outlet Diameter	50	65	80	100	150	200	250	300
Item								
Guide pipe dimensions	1" x (θ 30 x 2)			1.5" x (θ 45 x 2)			2" x (θ 55 x 2.5)	
Guide pipe length (mm)	-80							
Specification and quantity of expansion bolts	M12 x 80 x 2				M14 x 100 x 2		M16 x 120 x 2	
Specification and quantity of anchor bolts	M16 x 250 x 4						M20 x 300 x 4	
Size of hole reserved for anchor bolt	80 x 80 x 300						100 x 100 x 350	
Inner diameter of rubber hose (mm)	50	65	80	100	150	200	250	300