
Data sheet: Wilo-Multivert MVI 110 (1~230 V, FKM, PN 25)


Pump curves



Pump curves in accordance with ISO 9906, class 2

Terminal diagram


Single-phase current



1~230 V

Terminal diagram

Single-phase current at wrong direction of rotation



1~230 V

ErP READY — APPLIES TO EUROPEAN DIRECTIVE FOR ENERGY RELATED PRODUCTS

Power		
Fluid temperature	T	-15...+90 °C
Max. ambient temperature	T	40 °C
Maximum operating pressure	p_{max}	25 bar
Minimum Efficiency Index (MEI)		
Minimum Efficiency Index (MEI)		≥ 0.40
Motor		
Insulation class		F
Protection class		IP55
Mains connection		1~230 V, 50 Hz
Nominal motor power	P_2	1.1 kW
Power consumption	P_1	1.49 kW
Nominal current 1~230 V, 50 Hz	I_N	6.6 A
Motor efficiency	η_m 100%	73.0 %
Connections		
Flange nominal diameter (on the pressure side)		DN 25
Flange nominal diameter (on the suction side)		DN 25
Rated pressure level (on the pressure side)	PN	PN 25
Rated pressure level (on the suction side)	PN	PN 25
Materials		
Impeller		1.4404 [AISI316L]
Pump housing		1.4404 [AISI316L]
Pump shaft		1.4404 [AISI316L]
Static seal		FKM
Mechanical seal		U3BVGG
Information for order placements		
Make		Wilo
Type		MVI 110
Art no.		4070543
Weight approx.	m	29.6 kg

• = available, - = not available