
3 SDM 2



Performance Data 50 Hz

VERSION		MODEL	P2		CAP µf	DELIVERY									
1*	2**	220V ~ 1 Phase	kW	HP		m3/h	0	0.3	0.6	0.9	1.2	1.5	1.8	2.1	2.4	2.7
						l/min	0	5	10	15	20	25	30	35	40	45
√	√	3SDM2/8	0.18	0.25	16	Head (m)	35	34	34	33	32	29	26	22	17	11
√	√	3SDM2/11	0.25	0.39	16		48	47	47	46	44	40	36	30	24	15
√	√	3SDM2/15	0.37	0.5	20		65	64	64	63	60	55	49	41	33	21
√	√	3SDM2/21	0.55	0.75	25		91	90	90	88	84	77	68	58	46	29
√	√	3SDM2/27	0.75	1	35		117	116	115	113	107	99	88	75	59	38
√		3SDM2/33	1.1	1.5	45		143	142	141	138	131	121	107	91	72	46
√		3SDM2/39	1.1	1.5	45		168	167	166	163	155	143	127	108	85	55
√		3SDM2/47	1.5	2	55		203	202	201	196	187	172	153	130	102	66

* Version 1 Pump, Motor & Control Box
** Version 2 Pump, Motor, Control Box, Base plate, Cable (length - refer price list), Joint & Rope.

Note: Unit c/w maximum 1.5mm 4 core cable.
However, it is not recommended for use for lengths longer than 60m.
For applications where longer distances are required it is advised to purchase the Version 1 kit. Refer to the 3" & 4" Borehole Catalogue (p.7) for the cable length chart to ensure correct cable size is purchased.