



## Performance Data 50Hz

MODEL (50Hz)		P2		Delivery											
1 - 220-240V	3 - 380 - 415V	kW	HP	m³/h		n≈2850 1/min									
				l/min	0	1.2	2.4	3.6	4.8	6.0	7.2	8.4			
4SDM6/5	4SD6/5	0.37	0.5	HEAD (m)	36	34	33	31	28	24	19	12			
4SDM6/6	4SD6/6	0.55	0.75		43	41	39	37	34	29	23	15			
4SDM6/8	4SD6/8	0.75	1		58	54	52	50	45	38	30	20			
4SDM6/11	4SD6/11	1.1	1.5		80	74	72	69	62	52	41	27			
4SDM6/12	4SD6/12	1.5	2		87	81	79	75	68	57	45	29			
4SDM6/15	4SD6/15	1.5	2		101	95	92	87	79	67	53	34			
4SDM6/17	4SD6/17	2.2	3		123	115	111	106	96	81	64	42			
4SDM6/20	4SD6/20	2.2	3		145	135	131	125	113	95	75	49			
-	4SD6/23	3	4		166	156	151	143	130	110	87	56			
-	4SD6/26	3	4		188	176	171	162	147	124	98	63			
-	4SD6/30	4	5.5		217	203	197	187	170	143	113	73			
-	4SD6/34	4	5.5		246	230	223	212	193	162	128	83			
-	4SD6/38	5.5	7.5		275	257	249	237	216	181	143	93			
-	4SD6/42	5.5	7.5		304	284	275	262	238	200	158	103			
-	4SD6/47	7.5	10		340	318	308	293	267	224	177	115			
-	4SD6/52	7.5	10		376	352	341	324	295	248	196	127			