



MODEL		DN	DIMENSIONS (mm)					WEIGHTS (kg)				
1 - 220-240V	3 - 380 - 415V		P	M(S)	M(T)	T(S)	T(T)	P	M(S)	M(T)	T(S)	T(T)
4SDM6/5	4SD6/5	1 3/4"	400	314	314	714	714	3.0	6.7	6.7	9.7	9.7
4SDM6/6	4SD6/6	1 3/4"	435	329	329	764	764	3.3	7.3	7.3	10.6	10.6
4SDM6/7	4SD6/7	1 3/4"	469	344	344	813	813	3.6	8.0	8.0	11.6	11.6
4SDM6/8	4SD6/8	1 3/4"	504	359	344	863	848	3.8	8.7	8.0	12.5	11.8
4SDM6/9	4SD6/9	1 3/4"	538	379	379	917	917	4.1	9.8	9.8	13.9	13.9
4SDM6/11	4SD6/11	1 3/4"	607	399	379	1006	986	4.7	10.6	9.8	15.3	14.5
4SDM6/12	4SD6/12	1 3/4"	642	424	424	1066	1066	5.0	11.7	11.7	16.7	16.7
4SDM6/14	4SD6/14	1 3/4"	742	449	424	1191	1166	5.6	12.9	11.7	18.5	17.3
4SDM6/17	4SD6/7	1 3/4"	846	502	514	1348	1360	6.4	15.7	15.7	22.1	22.1
4SDM6/20	4SD6/20	1 3/4"	949	542	514	1491	1463	7.3	17.7	15.7	25.0	23.0
4SDM6/23	4SD6/23	1 3/4"	1053	594	554	1647	1607	8.1	19.8	17.7	27.9	25.8
-	4SD6/26	1 3/4"	1156	-	594	-	1750	9.0	-	19.8	-	28.8
-	4SD6/30	1 3/4"	1326	-	658	-	1984	1.01	-	21.4	-	31.5
-	4SD6/34	1 3/4"	1464	-	698	-	2162	11.3	-	23.7	-	35.0
-	4SD6/38	1 3/4"	1602	-	738	-	2340	12.4	-	25.5	-	37.9
-	4SD6/42	1 3/4"	1740	-	788	-	2528	13.6	-	28.0	-	41.6
-	4SD6/47	1 3/4"	1944	-	848	-	2792	15.0	-	30.0	-	45
-	4SD6/52	1 3/4"	2116	-	908	-	3024	16.4	-	34.0	-	50.4
4SDM8/5	4SD8/5	1 3/4"	418	329	329	747	747	3.0	7.3	7.3	10.3	10.3
4SDM8/6	4SD8/6	1 3/4"	456	344	344	800	800	3.2	8.0	8.0	11.2	11.2
4SDM8/7	4SD8/7	1 3/4"	494	359	344	853	838	3.6	8.7	8.0	12.3	11.6
4SDM8/8	4SD8/8	1 3/4"	532	379	379	911	911	3.9	9.8	9.8	13.7	13.7
4SDM8/9	4SD8/9	1 3/4"	570	399	379	969	949	4.2	10.6	9.8	14.8	14.0
4SDM8/10	4SD8/10	1 3/4"	609	424	424	1033	1033	4.5	11.7	11.7	16.2	16.2
4SDM8/12	4SD8/12	1 3/4"	717	449	424	1165	1141	5.1	12.9	11.7	18.0	16.8
4SDM8/14	4SD8/14	1 3/4"	793	502	514	1295	1307	5.7	15.7	15.7	21.4	21.4
4SDM8/17	4SD8/17	1 3/4"	907	542	514	1449	1421	6.6	17.7	15.7	24.3	22.3
4SDM8/20	4SD8/20	1 3/4"	1021	594	554	1615	1575	7.5	19.8	17.7	27.3	25.2
-	4SD8/23	1 3/4"	1136	-	594	-	1730	8.4	-	19.8	-	28.2
-	4SD8/26	1 3/4"	1250	-	658	-	1908	9.2	-	21.4	-	30.6
-	4SD8/29	1 3/4"	1396	-	698	-	2094	10.1	-	23.7	-	33.8
-	4SD8/33	1 3/4"	1548	-	738	-	2286	11.3	-	25.5	-	36.8
-	4SD8/37	1 3/4"	1701	-	788	-	2489	12.5	-	28.0	-	40.5
-	4SD8/41	1 3/4"	1884	-	848	-	2732	13.7	-	30.0	-	43.7
-	4SD8/45	1 3/4"	2037	-	908	-	2945	14.9	-	34.0	-	48.9

\* M(S) is single phase motor, M(T) is three phase motor.

\* T(S) is single phase motor, T(T) is three phase motor.